

ARTICLE : PP 0001 - PP 0011

PRODUCT : PRO-Paint Construction marker (Fluorescent) 180°

Description

Construction marker Fluorescent is a very good visible marking paint. Multifunctional for construction and infrastructure to mark where holes must be drilled or where pipes have to be installed etc. Including safety cap. Lifespan of approx. 8-12 months, high covering ability, weather resistant and a high mechanical resistance. Suitable for application on substrates such as metal, concrete, stone, wood, masonry, gypsum blocks etc.

Applications

Metal	Masonry
Concrete	Wood
Dots	Fence poles/ tunnels/ with measuring equipment

Product references

Fast drying	180° valve (can be used upside down)
Fluorescent	Safety cap
Excellent adhesion	

Physical and Chemical Properties

Contents	:	500 ML
Base	:	Acrylic resin
Colour	:	Luminous rose, luminous red, luminous orange, luminous yellow, luminous blue, luminous green, white, black, red and yellow
VOC content	:	Approximately 87 m/m %
Solids content	:	Approximately 13 m/m %
Heat resistant	:	Up to 110°C
Use	:	1 to 2 m ² per 500ml, depending on substrate and application
Drying time	:	at 23°C and rel. humidity 65% Dust-dry after 5 to 10 minutes Touch-dry after 10 to 20 minutes Hardened/ resprayable after 24 hrs (Depending on ambient temperature, humidity and layer thickness)
Storage / Shelf life	:	At least 12 months in tightly closed original packaging on dry, cool and frost-free place.
General	:	Do not use below 10°C. Do not apply outside if threatening rain, frost or in full sunlight. Never place aerosol can on heat source.

Instructions for use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Cover the surrounding area if preferred. The aerosol can should be at room temperature. Ideal processing temperature 15 to 25°C. Shake the aerosol can well for 2 minutes before use and spray a sample. Distance to the surface to be treated should be approximately 25 to 30 centimetres. Also, shake occasionally during use. You can use this aerosol can upside down. After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).