

**ARTICLE : PT 0002**

**PRODUCT : PRO-Tech Silicone spray**

## Description

*Silicone spray to lubricate and protect of parts of metal, plastic and rubber. Silicone spray is water-repellent, pH neutral and resistant against weather influences and weak acids and alkalis. Silicone spray prevents freezing and drying out of rubber parts and the squeaking and cracking of plastic parts. Silicone spray has an excellent mechanical and thermal stability. PRO-Tech Silicone spray has a directed spray pattern and can withstand temperatures from - 50°C to + 200°C.*

## Applications

Squeaky plastic parts	Door rubbers
Dashboards	Bumpers
Guide rails (caravan, sun blinds)	Sunroofs
Sliding doors	Saw blades
Tool for unloading moulds	

## Product references

Excellent adhesion  
Water-repellent  
Prevents freezing and drying out of rubber parts  
Prevents squeaking and cracking of plastic parts  
Excellent mechanical and thermal stability  
Resistant against weather influences  
Resistant against weak acids and alkalis  
Directed spray pattern

## Physical and Chemical Properties

Contents	:	400 ML
Base	:	Silicon Oil (1,000 cSt)
Appearance	:	Clear colourless liquid
Propellant	:	Propane-Butane
VOC-CH %	:	88%
VOC-EU g/l	:	580 g/l
Specific gravity (g/ml 20°C)	:	0.659
Vapour pressure at 20°C	:	3-4 bar
Spraying flow rate	:	1.5 g/sec
Temperature resistant	:	-50°C to +200°C
pH value	:	Neutral

## Instructions for use

**Before use, carefully read the instructions on the packaging and act accordingly.**

The aerosol can should be at room temperature. The ideal processing temperature is from 5 to 30°C. Shake the aerosol can before use. Apply the silicone spray in a thin layer. The best lubrication is obtained after evaporation of the solvent (approximately 1 minute).