

ARTICLE : PT 0012

PRODUCT : PRO-Tech Paint stripper

Description

PRO-Tech Paint stripper is a highly professional and intensive methylene chloride-free fast acting paint stripper. Applicable for us on virtually any surface and especially suitable for removing alkyd paint, waterborne paint, 1 or 2-components epoxy and polyurethane coatings etc.

Applications

Alkyd paint	Bitumen
Waterborne paint	Sealants
1 and 2 components coatings	Adhesives
Graffiti	Wood, mineral and metal surface

Product references

Methylene chloride-free!	Biodegradable
Fast acting	Active on all types of paint
Contains no acids, alkalis, NMP, methylene chloride, biocides and preservatives	
Fan nozzle to apply material evenly	

Physical and Chemical Properties

Contents	:	500ML
Base	:	Mix of solvents and paraffin wax
Propellant	:	DME
VOC-CH %	:	100%
VOC-EU g/l	:	794 g/l
Specific gravity (g/ml 20°C)	:	0.794
Vapour pressure at 20°C	:	3.3 - 3.9 bar
Spraying flow rate	:	2.5 g/sec
pH value	:	Approximately 8
Use / dosing	:	2-3 m ² /kg, depending on object and processing method and severity of dirt
Storage / Shelf life	:	At least 12 months in tightly closed original packaging on dry, cool and frost-free place
General	:	Do not use below 5°C. Surface must be frost-free. At low temperatures the effect is delayed

Instructions for use

Before use, carefully read the instructions on the packaging and act accordingly.

Cover / protect the surrounding area. Aerosol can should be at room temperature. Processing temperature should be between 5°C and 25°C. Apply the product in a sufficient layer thickness on the surface to be treated. Leave the product for at least 15 minutes. Adjust the exposure time for 2-components coatings. Brush, or spray clean with (hot) water under an appropriate high pressure. Remove dissolved paint residue with a scraper or putty knife. If required, repeat the treatment. Rinse with water. Treat as industrial waste, provided fully empty and dry and otherwise in accordance with the Environmental Management Act.