

**ARTICLE : PP 0630 - PP 0637**

**PRODUCT : PRO-Paint Marking paint 600ML**

## Description

*High-quality marker spray for use on stone, concrete, asphalt and metal. A much used product in infrastructure.*

## Applications

Concrete	Asphalt
Stone	Dots
Metal	Fencing
Write	

## Product references

Very high covering ability	180° valve (can be used upside down)
Long lasting adhesion	Wear resistant
To use in PRO-Paint accessories	Fast drying
Resistant against petrol, chemicals and weather influences	

## Physical and Chemical Properties

Contents	:	600 ML
Base	:	Acrylic resin
Colour	:	White/yellow/black/green/blue/orange/red/luminous pink
Colours closest to RAL	:	White (RAL 9003 / RAL9016) Yellow (RAL 1018) Black (RAL 9004) Green (RAL 6032) Blue (RAL 5015) Orange (RAL 2004) Red (RAL 3000)
VOC content	:	Approximately 70 m/m %
Solids content	:	Approximately 30 m/m %
Capacity	:	Approximately 60 metres, depending on substrate and processing method
Drying time	:	Hardened after 16 hrs (Depending on ambient temperature, humidity and layer thickness)
Storage / Shelf life	:	At least 12 months in tightly closed original packaging on dry, cool and frost-free place.
General	:	Do not use below 10°C. Do not apply outside if threatening rain, frost or in full sunlight. Never place aerosol can on heat source.

## Instructions for use

**Before use, carefully read the directions on the packaging and act accordingly.**

The surface should be clean, dry and free of grease. The aerosol can should be at room temperature. Ideal processing temperature 15 to 25°C. Shake the aerosol can well for 2 minutes before use and spray a sample. Apply the marker spray in the desired width. The aerosol can works in 180° / can be used upside down. After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).