

ARTICLE : PP 0705

PRODUCT : PRO-Tech Impregnation Spray

Description

High-quality impregnation agent for protection against moisture and dirt adhesion. The unique formula creates an invisible, protective film layer. This ensures that the surface is oil and water repellent and the reattachment of dirt is effectively prevented. The product is air permeable.

Applications

Joints	Porous and non-porous surfaces
Natural stone	Ceramics
For indoor and outdoor use	Bathrooms and kitchens
Tents	Shoes
Sun blinds	(Rain) clothing
(Garden) furniture	

Product references

Water-repellent	Does not stain
Air permeable	Invisible
Prevents dirt adhesion	Fast drying
Long-term protection	
User-friendly	

Physical and Chemical Properties

Contents	:	600 ML
Base	:	Fluorocarbon
Appearance	:	Clear colourless liquid
Propellant	:	Propane-Butane
VOC-CH %	:	100%
VOC-EU g/l	:	697 g/l
Specific gravity (g/ml 20°C)	:	0.697
Vapour pressure at 20°C	:	3.7-4.3 bar
Spraying flow rate	:	1.7 g/sec
Drying time	:	Approximately 1 hour

Instructions for use

Before use, carefully read the instructions on the packaging and act accordingly.

The aerosol can should be at room temperature.

The ideal processing temperature is from 5 to 30°C.

Shake the aerosol can before use.

The surface must be clean and dry.

Spray the parts to be treated in thin layers with an interim drying time of 5 to 10 minutes.