

ARTICLE : PP 0200

PRODUCT : PRO-Paint Zinc spray Alu fast drying

Description

Zinc spray Alu fast drying is a fast drying cold galvaniser/ repair paint that ensures shine restoration of galvanised steel. It gives the appearance of new galvanised steel and is therefore ideal for minor maintenance work and repairs. Gives proper protection for bare steel and galvanised steel. Heat resistant to 110°.

Applications

Iron
Steel

Product references

Fast drying
Ideal for touching up new galvanised steel
Fast shine restoration of galvanised steel
Excellent adhesion

Physical and Chemical Properties

Contents	:	500 ML
Base	:	Acrylate
Colour	:	Aluminium shine
VOC content	:	Approximately 90 m/m %
Solids content	:	Approximately 10 m/m %
Heat resistant	:	Up to 110°C
Use	:	1 to 2 m ² per layer, depending on object and processing method
Drying time	:	at 23°C and rel. humidity 65% Dust-dry after 5 to 10 minutes Touch-dry after 10 to 20 minutes Hardened/ resprayable after 2 hrs (Depending on ambient temperature, humidity and layer thickness)
Storage / Shelf life	:	At least 12 months in tightly closed original packaging on dry, cool and frost-free place.
General	:	Do not use below 10°C. Do not apply outside if threatening rain, frost or in full sunlight. Never place aerosol can on heat source.

Instructions for use

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol can should be at room temperature. Ideal processing temperature 15 to 25°C. Shake the aerosol can well for 2 minutes before use and spray a sample. Distance to the surface to be treated should be approximately 25 to 30 cm. Apply PRO-Paint Zinc spray Alu fast drying in several thin layers. Before applying the next layer, shake the aerosol can again. After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).