

ARTICLE : PT 0003

PRODUCT : PRO-Tech Penetrating oil

Description

High-quality, effective tool for loosening stuck and rusted parts. Penetrating oil has good penetrating properties and contains graphite and MoS₂. Penetrating oil is moisture repellent and corrosion-resistant. PRO-Tech Penetrating oil has a directed spray pattern and can be used at any angle.

Applications

Hinges/locks	Tools
Screw connections	Guide rails
Sprockets	Chains
Locks	Garden tools
Fixing materials	Spinning reels
(screws, bolts and nuts)	Hinges

Product references

Good penetrating properties	Contains graphite and MoS ₂
Moisture repellent	Corrosion-resistant
Directed spray pattern	360° valve

Physical and Chemical Properties

Contents	:	400 ML
Base	:	Aliphatic and aromatic hydrocarbons, low viscosity mineral oils, anti-corrosion additives and graphite and MoS ₂
Appearance	:	Black liquid
Propellant	:	Propane-Butane
VOC-CH %	:	90%
VOC-EU g/l	:	652 g/l
Specific gravity (g/ml 20°C)	:	0.728
Vapour pressure at 20°C	:	2.0-2.6 bar
Spraying flow rate	:	1.5 g/sec

Instructions for use

Before use, carefully read the instructions on the packaging and act accordingly.

The aerosol can should be at room temperature.

The ideal processing temperature is from 5 to 30°C.

Shake the aerosol can before use.

Apply penetrating oil and leave on for a while.