

ARTICLE : PT 0021

PRODUCT : PRO-Tech Shockspray

Description

High-quality, effective tool for loosening stuck and rusted parts. By shocking the affected parts with a fast temperature drop, the jammed connection "breaks", after which the part can be disassembled more easily. PRO-Tech Shockspray has a directed spray pattern and can be used at any angle (360°).

Applications

Screws, bolts and nuts
Screw connections
Fixing materials

Tools
Sprockets
Hinges and locks

Product references

Shock effect
Fast acting
Moisture repellent
360° valve

Penetrating properties
Briefly lowers the temperature to -30°C
Corrosion-resistant
Directed spray pattern

Physical and Chemical Properties

Contents	:	200 ML
Base	:	Aliphatic and aromatic hydrocarbons, low viscosity mineral oils, anti-corrosion additives and ultrafine particles.
Appearance	:	Clear red liquid
Propellant	:	Propane-Butane
VOC-CH %	:	97%
VOC-EU g/l	:	580 g/l
Specific gravity (g/ml 20°C)	:	0.596
Vapour pressure at 20°C	:	3.9-4.5 bar
Spraying flow rate	:	+/- 2 g/sec

Instructions for use

Before use, carefully read the instructions on the packaging and act accordingly.

The aerosol can should be at room temperature.

The ideal processing temperature is from 5 to 30°C.

Shake the aerosol can before use.

Spray the screw connection to be treated for a few seconds by briefly pressing the spray button several times. Due to the severe temperature drop, in conjunction with the penetrating operation of the oil, the screw connection can be loosened.