

ARTICLE : PT 0112

PRODUCT : PRO-Tech Gas leak finder

Description

PRO-Tech Gas leak finder is a high-quality product for the detection of leakages in gas pipes. User-friendly, fast and safe. The gas leak finder is inflammable and non-corrosive. It can be removed with water and is environmentally friendly. Gas leak finder is slightly alkaline and light foaming. PRO-Tech Gas leak finder can be used at any angle (360°).

Applications

| | |
|------------------------|-------------|
| Compressed air systems | Connectors |
| Gas pipes | Compressors |
| Air lines | Tyres |
| Flanged connections | |

Product references

Inflammable
Slightly alkaline
Light foaming
Non-corrosive
High efficiency
Easily removed with water
360° valve

Physical and Chemical Properties

| | | |
|------------------------------|---|---|
| Contents | : | 300 ML (400ML size) |
| Base | : | Mix of surface-active agents and corrosion inhibitors |
| Appearance | : | Clear colourless light foaming liquid |
| Propellant | : | Nitrogen |
| VOC-CH % | : | 15% |
| VOC-EU g/l | : | 152 g/l |
| Specific gravity (g/ml 20°C) | : | 1.017 |
| Vapour pressure at 20°C | : | 7.5-8.0 bar |
| Spraying flow rate | : | 4.4 g/sec |

Instructions for use

Before use, carefully read the instructions on the packaging and act accordingly.

Store frost free.

The aerosol can should be at room temperature.

The ideal processing temperature is 5 to 30°C.

Shake the aerosol can before use.

Apply leak finder on the suspected area to trace the leakage. Bubbles appear at the location of the leakage. Remove residue with water.